

NOIDA S E Z AUTHORITY

(Under Government of India)

Min. of Commerce & Industry, Deptt. of Commerce,
Noida Dadri Road, Phase-II, NOIDA-201305, Distt. Gautam Budh
Nagar (UP)

No. NSEZA/Admn./03/2009/

dt. 29.09/2014

Notice inviting Tenders

On behalf of Chairman & CEO; Noida SEZ Authority, Technical & Financial bids are invited from eligible Companies /Firms/Govt. bodies having at least 3 years experience in the field of Civil, Electrical, Painting etc. works in the Government / Semi Government Department or Individual Township/Companies for the following works as per annexure-A and B in NSEZ, Phase – II, Noida, Distt.- Gautam Budh Nagar (Uttar Pradesh). The tenders should reach to this office on or before 09.10.2014 up to 3.00 P.M. and the same shall be opened on the same day at 3.30 P.M. in the conference hall of NSEZ Phase- II, Noida. Earnest Money is required in the shape of DD from any Scheduled Bank in favour of "Noida SEZ Authority". The same shall be enclosed with technical tenders.

No Tender document has been prescribed. Bidder may submit their tenders on their letter head as per details given below:

The tender shall be on two bid system, where techno-commercial details shall be put into envelope no. (1) & price bid shall be put into envelop no. (2) separately for Annexre-A and Annexure-B. These both envelopes after being sealed properly shall be put in to envelope No (3) which should be properly sealed, before it is put in to the tender box. Envelope No (1) shall contain all details about experience, copy of registration, PAN, income tax returns for last 3 years duly audited. Tender of contractors who do not qualify the technical criteria shall be summarily rejected and their price bids shall not be opened. Authority can reject any or all-tenders without assigning any reasons.

S.	Scope of the Work	Estimated cost	Earnest	Time of
No.			Money	Comple
				tion
1.	As per Annexure - A,	₹ 5,00,000.00	₹ 50, 000/-	10 days
	(Work for Gate No. 2)			
2.	As per Annexure-B	₹ 1,75,000/-	₹ 17,500/-	10 days
	(Work for CWC)			

(Secretary)

Annexure-A

REPAIR WORK, GATE 2 STANDARD DSR SCHEDULE- CIVIL

		STANDARD DSR SCHEDULE- (JIVIL			1
S.No.	DSR-13 Code	Description of Item	Quant	tity	Rate (Rs)	Unit
S		l Earth Work				
6	ub-neau . I	Earth work in excavation by mechanical means (Hydraulic excavator) / manual means over areas (exceeding 30cm in depth. 1.5m in width as well as 10 sqm on plan) including disposal of excavated earth, lead up to 50m and lift up to 1.5m,disposed earth to be levelled and neatly dressed.				
a)	2.6.1	All kinds of soil	10.00	Cum	146.50	
25	2.25	Filling available excavated earth (excluding rock) in trenches, plinth, sides of foundations etc. in layers not exceeding 20cm in depth, consolidating each deposited layer by ramming and watering, lead up to 50 m and lift up to 1.5 m.		Cum	101.50	One Cubic Metre
35		Supplying chemical emulsion in sealed containers including delivery as specified.				
a)	2.34.1	Chlorpyriphos/ Lindane emulsifiable concentrate of 20%	20.00	Ltr	185.95	One Litre
36		Diluting and injecting chemical emulsion for POST-CONSTRUCTIONAL anti-termite treatment (excluding the cost of chemical emulsion):				
d)		Treatment of existing masonry using chemical emulsion @ one litre per hole at 300 mm interval including drilling holes at 45 degree and plugging them with cement mortar 1:2 (1 cement : 2 coarse sand) to the full depth of the hole :				
(i)	2.35.4.1	With Chlorpyriphos/Lindane E.C. 20% with 1% concentration.	100.00	m	16.00	One Running Metre
			Total	of the	Sub-Head - I	Earth Work :
	ub-Head : E			_	1	
136		Brick work with common burnt clay machine moulded F.P.S. (non modular) bricks of class designation 12.5 in exposed brick work including making horizontal and vertical grooves 10 mm wide 12 mm deep complete in cement mortar 1:6 (1 cement: 6 coarse sand).				
a)	6.29.1	From ground level upto plinth level.	4.00	Cum	4501.30	One Cubic Metre

DSR-13 Page 1 of 10

S.No.	DSR-13 Code	Description of Item	Quan	tity	Rate (Rs)	Unit	
			Tota	l of the S	Sub-Head -	Brick Work :	
S	ub-Head : I	Marble & Granite Work					
190		Providing and fixing 18mm thick gang saw cut mirror polished premoulded and prepolished) machine cut for kitchen platforms, vanity counters, window sills, facias and similar locations of required size of approved shade, colour and texture laid over 20mm thick base cement mortar 1:4 (1 cement : 4 coarse sand) joints treated with white cement, mixed with matching pigment, epoxy touch ups, including rubbing, curing, moulding and polishing to edges to give high gloss finish etc. complete at all levels.					
b)		Granite of any colour and shade					
(ii)	8.2.2.2	Area of slab over 0.50 sqm.	180.00	Sqm	3769.70	Two Square Metre	
191		Providing edge moulding to 18mm thick marble stone counters, Vanities etc. including machine polishing to edge to give high gloss finish etc. complete as per design approved by Engineer-in-Charge.					
b)	8.3.2	Granite work.	45.00	metre	210.65	Three Running Metre	
196		Providing and fixing expansion hold fasteners on C.C. /R.C.C./Brick masonry surface backing including drilling necessary holes and the cost of bolt etc complete.					
a)		Wedge expansion type					
(ii)	8.8.1.2	Fastener with threaded dia 10 mm.	600.00	No.	27.55	Each	
<u> </u>	<u> </u>	l l	of the Sub-	Head - N	Marble & Gi	ranite Work :	
	ub-Head : \ 	Wood and PVC Work					
242		Providing and fixing nickel plated M.S. pipe curtain rods with nickel plated brackets :					
b)	9.47.2	25 mm dia (heavy type)	25.00	m	126.00	One Running Metre	
256		Providing M.S. Piano hinges ISI marked IS: 3818 finished with nickel plating and fixing with necessary screws etc., complete.					
a)	9.61.1	Overall width 35 mm.	4.00	m	157.80	One Running Metre	

DSR-13 Page 2 of 10

S.No.	DSR-13	Description of Itom	Quan	tity,	Rate (Rs)	Unit
3.NO.	Code	Description of Item	Quan	LILY	Rate (RS)	Unit
263		Providing and fixing oxidised M.S. casement stays				
		(straight peg type) with necessary screws etc.				
		complete.				
a)	9.68.1	300 mm weighing not less than 200 gms.	6.00	No.	32.50	Each
267		Providing and fixing bright finished brass butt hinges				
		with necessary screws etc. complete :				
a)	9.72.1	125x85x5.5 mm (heavy type)	5.00	No.	395.00	Each
c)	9.72.3	100x85x5.5 mm (heavy type)	7.00	No.	345.60	Each
e)	9.72.5	75x65x4 mm (heavy type)	10.00	No.	130.15	Each
269		Providing and fixing bright finished brass tower bolts				
		(barrel type) with necessary screws etc. complete:				
a)	9.74.1	250x10 mm	8.00	No.	288.30	Each
c)	9.74.3	150x10 mm	5.00	No.	186.05	Each
271	9.76	Providing and fixing bright finished brass 100 mm	3.00	No.	514.55	Each
		mortise latch and lock with 6 levers and a pair of				
		lever handles of approved quality with necessary				
		screws etc. complete.				
277	9.82	Providing and fixing bright finished brass hanging	10.00	No.	79.60	Each
		type floor door stopper with necessary screws, etc.				
		complete.				
279	9.84	Providing and fixing aluminium extruded section	6.00	No.	1027.20	Each
		body tubular type universal hydraulic door closer				
		(having brand logo with ISI, IS: 3564, embossed on				
		the body, door weight upto 36 kg to 80 kg and door				
		width from 701 mm to 1000mm) with double speed				
		adjustment with necessary accessories and screws				
		etc. complete.				
285		Providing and fixing special quality chromium plated				
		brass cupboard locks with six levers of approved				
		quality with necessary screws etc. complete.				
c)	9.90.3	Size 65 mm	6.00	No.	183.50	Each
286	9.91	Providing and fixing chromium plated brass 50 mm	6.00	No.	62.70	Each
		cupboard or wardrobe knobs with nuts complete.				
287		Providing and fixing chromium plated brass handles			+ +	
		with necessary screws etc. complete:				
a)	9.92.1	125 mm	3.00	No.	210.95	Each
b)	9.92.2	100 mm	4.00	No.	181.55	Each
309		Providing and fixing magnetic catcher in cupboard /				
		ward robe shutters including fixing with necessary				
		screws etc. complete :				
b)	9.114.2	Double strip (horizontal type).	4.00	No.	22.55	Each

DSR-13 Page 3 of 10

S.No.	DSR-13	Description of Item	Quant	·i+v	Rate (Rs)	Unit			
3.110.	Code	Description of Item	Quant	.icy	nate (NS)	Oilit			
310	9.115	Providing and fixing powder coated telescopic	2.00	sets	186.20	One set			
		drawer channels 300mm long with necessary screws							
		etc. complete as per directions of Engineer-in-							
		charge.	al of the Car	h II and	Wood Am	d Du a Wanta			
C.	Sub-Head : Flooring Total of the Sub-Head - Wood And Pvc Work :								
420	11.37	Providing and laying Ceramic glazed floor tiles	90.00	Sqm	822.10	One Square			
720	11.57	300x300 mm (thickness to be specified by the	30.00	Jqiii	022.10	Metre			
		manufacturer) of 1st quality conforming to IS:15622				Wictic			
		of approved make in colours such as White, Ivory,							
		Grey, Fume Red Brown, laid on 20 mm thick Cement							
		Mortar 1:4 (1 Cement : 4Coarse sand) including							
		pointing the joints with white cement and matching							
		pigment etc., complete.	T	etal of th	ha Suh-Haa	d - Flooring :			
Sı	ub-Head : R	onfing	10	nai oj ii	ie Sub-Med	a - Piooring.			
452	ab ricad i ii	Painting top of roofs with bitumen of approved							
.52		quality @ 17 kg per 10 sqm impregnated with a coat							
		of coarse sand at 60 cudm per 10 sqm including							
		cleaning the slab surface with brushes and finally							
		with a piece of cloth lightly soaked in kerosene oil							
		complete:							
a)	12.15.1	With residual type petroleum bitumen of grade VG -	330.00	sqm	117.80	One Square			
uj	12.13.1	10	330.00	34111	117.00	Metre			
						Wietre			
454		10 cm thick (average) mud phaska of damped brick							
		earth on roofs laid to slope consolidated and							
		plastered with 25 mm thick mud mortar with bhusha							
		@ 35 kg per cum of earth and gobri leaping with mix							
		1:1 (1 clay: 1 cow-dung) and covered with machine							
		moulded tile bricks, grouted with cement mortar 1:3							
		(1 cement : 3 fine sand) mixed with 2% of integral							
		water proofing compound by weight of cement and							
		finished neat.							
		Timshed fiedt.							
a)	12.17.1	with machine moulded common burnt clay FPS (non	100.00	Sqm	510.35	One Square			
,		modular) brick tiles of class designation 12.5,		'		Metre			
		conforming to IS 2690.							
455	12.18	Extar for every additional 1 cm thickness of mud	330.00	Sqm	10.15	One Square			
		phaska				Metre			
			<i>T</i>	otal of	the Sub-Hed	ud - Roofing :			
Sı	ub-Head : F	inishing							
503		20 mm cement plaster of mix :							

DSR-13 Page 4 of 10

S.No.	DSR-13	Description of Item	Quant	titv	Rate (Rs)	Unit
	Code	·				
a)	13.3.1	1:4 (1 cement: 4 fine sand)	20.00	Sqm	202.75	One Square Metre
506		20 mm cement plaster of mix :				
a)	13.6.1	1:4 (1 cement: 4 coarse sand)	20.00	Sqm	215.80	One Square Metre
a)	13.47.1	New work (Two or more coats applied @ 1.43 ltr/ 10 sqm. over and including priming coat of exterior primer applied @ 2.20 kg/10 sqm).	550.00	Sqm	90.00	One Square Metre
559		Wall painting with acrylic emulsion paint of approved brand and manufacture to give an even shade:				
a)	13.60.1	Two or more coats on new work.	300.00	Sqm	71.65	One Square Metre
			To	tal of th	e Sub-Head	- Finishing:
Sı	ub-Head : R	epairs to Buildings		•		
585		Repairs to plaster of thickness 12mm to 20mm in patches of area 2.5 sq. meters and under including cutting the patch in proper shape, raking out joints and preparing and plastering the surface of the walls complete including disposal of rubbish to the dumping ground within 50metres lead:				
a)	14.1.1	With cement mortar 1:4 (1 cement : 4 fine sand).	43.00	Sqm	221.15	One Square Metre
589		Renewing glass panes, with putty and nails wherever necessary including racking out the old putty:				
a)	14.5.1	Float glass panes of thickness 4 mm	3.00	Sqm	651.40	One Square Metre
b)	14.5.2	Float glass panes of thickness 5.5 mm	7.00	Sqm	868.60	One Square Metre
593	14.9	Renewal of old putty of glass panes (length)	30.00	m	21.20	One Running Metre
594	14.10	Refixing old glass panes with putty and nails	12.00	Sqm	275.30	One Square Metre

DSR-13 Page 5 of 10

S.No.	DSR-13	Description of Item	Quan	titv	Rate (Rs)	Unit
	Code	·				
597	14.13	Regrading terracing of mud phaska covered with tiles or brick, in cement by dismantling tiles or bricks, removing mud plaster, preparing the surface of mud phaska to proper slope, relaying mud plaster gobri leaping and tiles or bricks, grouted in cement mortar 1:3 (1 cement : 3 fine sand)including replacing unserviceable tiles or bricks with new ones and disposal of unserviceable material to the dumping ground (the cost of the new tiles or brick excluded) within 50 metres lead.	330.00	Sqm	253.15	One Square Metre
606		Renewing Wrought iron or M.S. Wheel or roller of steel door or gate and fitting and fixing the same with necessary clamps, nuts and bolts/welding and erection etc. complete.				
c)	14.33.3	100 mm	4.00	No.	119.45	Each
618	14.34	Providing and fixing 150 mm bright finished floor brass door stopper with rubber cushion, necessary brass screws etc. to suit shutter thickness complete	8.00	No.	210.35	Each
630	14.46	Removing dry or oil bound distemper, water proofing cement paint and the like by scrapping, sand papering and preparing the surface smooth including necessary repairs to scratches etc. complete.	800.00	Sqm	9.00	One Square Metre
632		Painting (two or more coats) on rain water, soil, waste and vent pipes and fittings with black anticorrosive bitumastic paint of approved brand and manufacture over and including a priming coat of ready mixed zinc chromate yellow primer on new work:				
a)	14.48.1	75 mm diameter pipes	30.00	m	22.95	One Running Metre
638		Painting with synthetic enamel paint of approved brand and manufacture of required colour to give an even shade:				
a)	14.54.1	One or more coats on old work.	25.00	Sqm	41.35	One Square Metre
		Tot	tal of the Si	ıb-Head	l - Repairs T	To Buildings:

Sub-Head: Dismantling and Demolishing

DSR-13 Page 6 of 10

C N -	DSR-13	Description of them	0		D-4- (D-)	11
S.No.	Code	Description of Item	Quant	iity	Rate (Rs)	Unit
659		Demolishing cement concrete manually/ by mechanical means including disposal of material within 50 metres lead as per direction of Engineer - in - charge.				
a)	15.2.1	Nominal concrete 1:3:6 or richer mix (i/c equivalent design mix)	2.00	Cum	806.35	One Cubic Metre
700		Dismantling manually/ by mechanical means including stacking of serviceable material and disposal of unserviceable material within50metres lead as per direction of Engineer-in-charge:				
b)	15.43.2	Bituminous road	120.00	Sqm	143.90	One Square Metre
713	15.56	Dismantling old plaster or skirting raking out joints and cleaning the surface for plaster including disposal of rubbish to the dumping ground within 50 metres lead.		Sqm	18.15	One Square Metre
717	15.60	Disposal of building rubbish / malba / similar unserviceable, dismantled or waste materials by mechanical means including loading, transporting, unloading to approved municipal dumping ground or as approved by Engineer-in-charge, beyond 50 m initial lead, for all loads including all lifts involved.		Cum	123.85	One Cubic Metre
		Total of the	Sub-Head -	Dismar	tling And L	Demolishing:
Sı	ub-Head : F	Road Work				
718	16.1	Preparation and consolidation of sub grade with power road roller of 8 to 12 tonne capacity after excavating earth to an average of 22.5 cm. depth, dressing to camber and consolidating with road roller including making good the undulations etc. and re-rolling the sub grade and disposal of surplus earth with lead upto 50 metres.		Sqm	73.55	One Square Metre

DSR-13 Page 7 of 10

S.No.	DSR-13	Description of Item	Quant	itv	Rate (Rs)	Unit
	Code	· ·		-		
787	16.69	Providing and laying at or near ground level factory made kerb stone of M-25 grade cement concrete in position to the required line, level and curvature, jointed with cement mortar 1:3 (1 cement: 3 coarse sand), including making joints with or without grooves (thickness of joints except at sharp curve shall not to more than 5mm), including making drainage opening wherever required complete etc. as per direction of Engineer-in-charge (length of finished kerb edging shall be measured for payment). (Precast C.C. kerb stone shall be approved by Engineer-in-charge).	1.00	Cum	5236.95	One Cubic Metre
799		Providing and erecting 2.00 metre high temporary barricading at site as per drawing/ direction of Engineer-in-Charge which includes writing and painting, arrangement for traffic diversion such as traffic signals during construction at site for day and night, glow lamps, reflective signs, marking, flags, caution tape as directed by the Engineer-in-Charge. The barricading provided shall be retained in position at site continuously i/c shifting of barricading from one location to another location as many times as required during the execution of the entire work till its completion. Rate include its maintenance for damages, painting, all incidentals, labour materials, equipments and works required to execute the job. The barricading shall not be removed without prior approval of Engineer-in-Charge.				

DSR-13 Page 8 of 10

6.11	DSR-13	5	0	••.	5 . (5)	
S.No.	Code	Description of Item	Quant	ity	Rate (Rs)	Unit
809		Providing and laying factory made coloured chamfered edge Cement Concrete paver blocks of required strength, thickness & size/shape, made by table vibratory method using PU mould, laid in required colour & pattern over 50mm thick compacted bed of fine sand, compacting and proper embedding/laying of inter locking paver blocks into the sand bedding layer through vibratory compaction by using plate vibrator, filling the joints with jamuna sand and cutting of paver blocks as per required size and pattern, finishing and sweeping extra sand in footpath, parks, lawns, drive ways or light traffic parking etc. complete as per manufacturer's specifications & direction of Engineer-in-Charge.				
	16.91	60mm thick C.C. paver block of M-35 grade with	120.00	Sqm	727.00	One Square
	16.91	approved colour, complete design & pattern.	120.00	Sqiii	727.00	Metre
			Tota	l of the	Sub-Head -	Road Work:
		Vater Proofing			1	
1065	22.12	Supplying and applying bituminous solution primer on roof and or wall surface at 0.24 litre per sqm.	330.00	Sqm	28.50	One Square Metre
			Total of	the Sub-	-Head - Wat	ter Proofing:
		lorticulture & Landscaping				
1075	23.1	Trenching in ordinary soil up to a depth of 60cm including removal and stacking of serviceable materials and then disposing of surplus soil, by spreading and neatly leveling within a lead of 50m and making up the trenched area to proper levels by filling with earth or earth mixed with sludge or/and manure before and after flooding trench with water(excluding cost of imported earth, sludge or manure).	10.00	Cum	37.10	
1076	23.2	Supplying and stacking of good earth at site including royalty and carriage upto 1 km (earth measured in stacks will be reduced by 20% for payment).	4.00	Cum	308.35	One Cubic Metre
1078		Supplying and stacking at site dump manure from approved source, including carriage upto 1 km (manure measured in stacks will be reduced by 8% for payment):				

DSR-13 Page 9 of 10

S.No.	DSR-13 Code	Description of Item	Quan	tity	Rate (Rs)	Unit
a)	23.4.1	Screened through sieve of I.S. designation 20mm	2.00	Cum	167.60	
1082	23.8	Spreading of sludge, dump manure and / or good earth in required thickness as per direction of Officer-in-charge (Cost of sludge, dump manure and / or good earth to be paid separately).	4.00	Cum	25.15	100 Square Metre
1083	23.9	Mixing earth and sludge or manure in the required proportion specified or directed by the Officer-in-charge	4.00	Cum	17.25	One Cubic Metre
1084		Grassing with selection No.1 grass including watering and maintenance of the lawn for 30 days or more till the grass forms a thick lawn, free from weeds and fit for mowing including supplying good earth, if needed (the good earth shall be paid for separately).				
a)	23.10.1	In rows 5 cm apart in both directions.	1.00	Units	841.25	100 Square Metre
1087	23.13	Preparation of beds for hedging and shrubbery by excavating 60cm deep and trenching the excavated base to a further depth of 30cm, refilling the excavated earth after breaking clods and mixing with sludge or manure in the ratio of 8:1 (8 parts of stacked volume of earth after reduction by 20%: one part of stacked volume of sludge or manure after reduction by 8%),flooding with water, filling with earth if necessary, watering and finally fine dressing, leveling etc. including stacking and disposal of materials declared unserviceable and surplus earth by spreading and leveling as directed, within a lead of 50 m, lift up to 1.5 m complete (cost of sludge, manure or extra earth to be paid for separately).		Cum	105.20	100 Square Metre
1102	23.28	Preparation of mounds of various size and shape by available excavated / supplied earth in layers not exceeding 20 cm in depth, breaking clods, watering of each layer, dressing etc., lead upto 50 meter and lift upto 1.5m complete as per direction of Officer-incharge.	3.00	No.	215.60	Each
		Total of the Sub-Head - Horticulture & Lo				
		Estmated Cost- (Rupees five la	cs only)			5.00 Lacs

DSR-13 Page 10 of 10

REPAIR WORK, CWC OFFICES STANDARD DSR SCHEDULE- CIVIL

S.No. Suk 242	Code b-Head : V	Description of Item	Quant	ritv	Data /Dat				
	b-Head : V		Quantity		Qualitity		Quantity Rate (Rs)		Unit
242		Vood and PVC Work			•				
		Providing and fixing nickel plated M.S. pipe curtain							
		rods with nickel plated brackets :							
b)	9.47.2	25 mm dia (heavy type)	36.00	m	126.00	One			
						Running			
						Metre			
263		Providing and fixing oxidised M.S. casement stays							
		(straight peg type) with necessary screws etc.							
	0.50.4	complete.			22.50				
a)	9.68.1	300 mm weighing not less than 200 gms.	3.00	No.	32.50	Each			
267		Providing and fixing bright finished brass butt hinges							
2)	9.72.1	with necessary screws etc. complete:	6.00	No.	395.00	Each			
a) c)	9.72.3	125x85x5.5 mm (heavy type) 100x85x5.5 mm (heavy type)	6.00	No.	345.60	Each			
e)	9.72.5	75x65x4 mm (heavy type)	5.00	No.	130.15	Each			
279	9.72.5	Providing and fixing aluminium extruded section	5.00	No.	1027.20	Each			
2/3	3.04	body tubular type universal hydraulic door closer	5.00	INO.	1027.20	Lacii			
		(having brand logo with ISI, IS : 3564, embossed on							
		the body, door weight upto 36 kg to 80 kg and door							
		width from 701 mm to 1000mm) with double speed							
		adjustment with necessary accessories and screws							
		etc. complete.							
		'							
286	9.91	Providing and fixing chromium plated brass 50 mm	2.00	No.	62.70	Each			
		cupboard or wardrobe knobs with nuts complete.							
292		Providing and fixing aluminium tower bolts ISI							
		marked anodised (anodic coating not less than grade							
		AC 10 as per IS : 1868) transparent or dyed to							
		required colour or shade with necessary screws etc.							
		complete :							
b)	9.97.2	250x10 mm	6.00	No.	90.65	Each			
d)	9.97.4	150x10 mm	4.00	No.	62.75	Each			
295		Providing and fixing aluminium handles ISI marked							
ı I		anodised (anodic coating not less than grade AC 10							
		as per IS: 1868) transparent or dyed to required colour or shade with necessary screws etc. complete							
b)	9.100.2	100 mm	6.00	No.	52.80	Each			

DSR-13 Page 1 of 4

S.No.	DSR-13 Code	Description of Item	Quantity		Rate (Rs)	Unit
296		Providing and fixing aluminium hanging floor door stopper ISI marked anodised (anodic coating not less than grade AC 10 as per IS: 1868)transparent or dyed to required colour and shade with necessary screws etc. complete.				
b)	9.101.2	Twin rubber stopper	8.00	No.	80.20	Each
309		Providing and fixing magnetic catcher in cupboard / ward robe shutters including fixing with necessary screws etc. complete:				
b)	9.114.2	Double strip (horizontal type).	2.00	No.	22.55	Each
310	9.115	Providing and fixing powder coated telescopic drawer channels 300mm long with necessary screws etc. complete as per directions of Engineer-incharge.	2.00	sets	186.20	One set
			al of the Su	b-Head	! - Wood An	nd Pvc Work:
	ub-Head : F			1	1	1
503	42.24	20 mm cement plaster of mix :	20.00		202.75	0 0
a)	13.3.1	1:4 (1 cement: 4 fine sand)	20.00	Sqm	202.75	One Square Metre
541		Distempering with oil bound washable distemper of approved brand and manufacture to give an even shade				
a)	13.41.1	New work (two or more coats) over and including water thinnable priming coat with cement primer.	700.00	Sqm	79.65	One Square Metre
544		Finishing walls with water proofing cement paint of required shade :				
a)	13.44.1	New work (Two or more coats applied @ 3.84 kg/10 sqm).	980.00	Sqm	54.40	One Square Metre
559		Wall painting with acrylic emulsion paint of approved brand and manufacture to give an even shade:				
a)	13.60.1	Two or more coats on new work.	100.00	Sqm	71.65	One Square Metre
561		Painting with synthetic enamel paint of approved brand and manufacture of required colour to give an even shade:	_			
a)	13.62.1	Two or more coats on new work over an under coat of suitable shade with ordinary paint of approved brand and manufacture.	240.00	Sqm	92.75	One Square Metre
			To	tal of th	e Sub-Head	! - Finishing:

DSR-13 Page 2 of 4

S.No.	DSR-13 Code	Description of Item	Quantity		Rate (Rs)	Unit		
Sub-Head : Repairs to Buildings								
585		Repairs to plaster of thickness 12mm to 20mm in patches of area 2.5 sq. meters and under including cutting the patch in proper shape, raking out joints and preparing and plastering the surface of the walls complete including disposal of rubbish to the dumping ground within 50metres lead:						
b)	14.1.2	With cement mortar 1:4 (1cement: 4 coarse sand).	30.00	Sqm	231.85	One Square Metre		
589		Renewing glass panes, with putty and nails wherever necessary including racking out the old putty:						
a)	14.5.1	Float glass panes of thickness 4 mm	2.00	Sqm	651.40	One Square Metre		
b)	14.5.2	Float glass panes of thickness 5.5 mm	6.00	Sqm	868.60	One Square Metre		
591		Renewing glass panes and refixing existing wooden fillets:						
b)	14.7.2	Float glass panes of thickness 5.5 mm	5.00	Sqm	906.35	One Square Metre		
593	14.9	Renewal of old putty of glass panes (length)	40.00	m	21.20	One Running Metre		
594	14.10	Refixing old glass panes with putty and nails	15.00	Sqm	275.30	One Square Metre		
630	14.46	Removing dry or oil bound distemper, water proofing cement paint and the like by scrapping, sand papering and preparing the surface smooth including necessary repairs to scratches etc. complete.	1200.00	Sqm	9.00	One Square Metre		
632		Painting (two or more coats) on rain water, soil, waste and vent pipes and fittings with black anticorrosive bitumastic paint of approved brand and manufacture over and including a priming coat of ready mixed zinc chromate yellow primer on new work:						
a)	14.48.1	75 mm diameter pipes	65.00	m	22.95	One Running Metre		

DSR-13 Page 3 of 4

S.No.	DSR-13	Description of Item	Quantity		Rate (Rs)	Unit			
	Code	Description of item			nate (no)	Oille			
		Total of the Sub-Head - Repairs To Buildings .							
Sı	Sub-Head: Dismantling and Demolishing								
713	15.56	Dismantling old plaster or skirting raking out joints	30.00	Sqm	18.15	One Square			
		and cleaning the surface for plaster including				Metre			
		disposal of rubbish to the dumping ground within 50							
		metres lead.							
717	15.60	Disposal of building rubbish / malba / similar unserviceable, dismantled or waste materials by		Cum	123.85	One Cubic Metre			
		mechanical means including loading, transporting,							
		unloading to approved municipal dumping ground or							
		as approved by Engineer-in-charge, beyond 50 m							
		initial lead, for all loads including all lifts involved.							
		Total of the Sub-Head - Dismantling And Demolishing:							
		Estimated Cost-Rs. One lac seventy five thounsand only				1,75,000/-			

DSR-13 Page 4 of 4